

To determine the proper load/inflation table, always refer to the markings on the tire sidewall for maximum load at cold pressure. Contact your Michelin dealer for tires with maximum loads and pressures other than indicated here.

Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes.

Therefore, printed material may not reflect the current load and inflation information.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration - 2 tires per axle. D = Dual configuration - 4 tires per axle.

WHEEL DIAMETER - 19.5"

225/70R19.5 LRF

PSI		65	70	75	80	85	90	95					MAXIMUM LOAD AND PRESSURE ON SIDEWALL	
kPa		450	480	520	550	590	620	660						
LBS	SINGLE	5510	5790	6080	6390	6630	6900	7280					S	3970 LBS at 95 PSI
LBS	DUAL	10400	10880	11440	12000	12460	12980	13660					D	3415 LBS at 95 PSI
KG	SINGLE	2500	2620	2760	2900	3000	3140	3300					S	1800 KG at 660 kPa
KG	DUAL	4720	4920	5200	5440	5640	5880	6200					D	1700 KG at 660 kPa

225/70R19.5 LRG

PSI		65	70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL	
kPa		450	480	520	550	590	620	660	690	720	760		
LBS	SINGLE	5510	5790	6080	6390	6630	6900	7280	7430	7690	7940	S	3970 LBS at 110 PSI
LBS	DUAL	10400	10880	11440	12000	12460	12980	13660	13960	14460	15000	D	3750 LBS at 110 PSI
KG	SINGLE	2500	2620	2760	2900	3000	3140	3300	3380	3480	3600	S	1800 KG at 760 kPa
KG	DUAL	4720	4920	5200	5440	5640	5880	6200	6320	6560	6800	D	1700 KG at 760 kPa

245/70R19.5 LRF

PSI		80	85	90	95							MAXIMUM LOAD AND PRESSURE ON SIDEWALL	
kPa		550	590	620	660								
LBS	SINGLE	7280	7480	7780	8160							S	4080 LBS at 95 PSI
LBS	DUAL	13660	14060	14620	15440							D	3860 LBS at 95 PSI
KG	SINGLE	3300	3400	3540	3700							S	1850 KG at 660 kPa
KG	DUAL	6200	6360	6640	7000							D	1750 KG at 660 kPa

245/70R19.5 LRH

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL	
kPa		520	550	590	620	660	690	720	760	790	830		
LBS	SINGLE	6780	7140	7500	7850	8200	8540	8880	9220	9550	9880	S	4940 LBS at 120 PSI
LBS	DUAL	12840	13520	14200	14860	15520	16160	16800	17440	18080	18700	D	4675 LBS at 120 PSI
KG	SINGLE	3080	3220	3400	3540	3720	3860	4000	4180	4300	4480	S	2240 KG at 830 kPa
KG	DUAL	5840	6120	6440	6720	7040	7320	7560	7920	8160	8480	D	2120 KG at 830 kPa

265/70R19.5 LRG

PSI		65	70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL	
kPa		450	480	520	550	590	620	660	690	720	760		
LBS	SINGLE	7230	7680	8110	8540	8970	9390	9800	10210	10620	11020	S	5510 LBS at 110 PSI
LBS	DUAL	13660	14500	15320	16140	16940	17740	18520	19300	20060	20820	D	5205 LBS at 110 PSI
KG	SINGLE	3280	3460	3700	3860	4080	4240	4460	4620	4780	5000	S	2500 KG at 760 kPa
KG	DUAL	6200	6520	6960	7280	7720	8040	8440	8720	9040	9440	D	2360 KG at 760 kPa

265/70R19.5 LRJ

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL	
kPa		520	550	590	620	660	690	720	760	790	830		
LBS	SINGLE	8250	8680	9110	9540	9960	10380	10790	11200	11610	12010	S	6005 LBS at 120 PSI
LBS	DUAL	15580	16420	17220	18040	18840	19620	20400	21180	21940	22700	D	5675 LBS at 120 PSI
KG	SINGLE	3740	3920	4140	4320	4540	4700	4860	5080	5240	5450	S	2725 KG at 830 kPa
KG	DUAL	7080	7400	7840	8160	8560	8880	9200	9600	9920	10300	D	2575 KG at 830 kPa

285/70R19.5 LRH

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL	
kPa		520	550	590	620	660	690	720	760	790	830		
LBS	SINGLE	8780	9250	9710	10160	10610	11050	11490	11930	12360	12790	S	6395 LBS at 120 PSI
LBS	DUAL	16500	17360	18220	19080	19920	20760	21580	22400	23220	24020	D	6005 LBS at 120 PSI
KG	SINGLE	3980	4180	4420	4600	4820	5000	5180	5400	5580	5800	S	2900 KG at 830 kPa
KG	DUAL	7480	7840	8280	8640	9080	9400	9720	10160	10480	10900	D	2725 KG at 830 kPa

LOAD / INFLATION TABLES